



CUT 40 / CUT 80

(Inbuilt Air Compressor)

FEATURES

- High frequency arc starting, easy to start arc.
- The incision to neat, smooth, and the effect is good.
- Self locking/ non self-locking cutting state.
- Using advanced IGBT inverter technology for precise feedback control, the current output is stable.

TECHNICAL SPECIFICATION:

| Model | CUT 40 | CUT 80 |
|-----------------------------------|---------------------|---------------------|
| Input voltage | 1 PH 220V \pm 15% | 3 PH 415V \pm 15% |
| Rated input capacity | 5.1KVA | 21.4KVA |
| Duty cycle | | 60% |
| Current adjust range | 10-40A | 20-80A |
| Power factor | | 0.95 |
| The cutting gun uses air pressure | | 0.45 |
| Max cutting thickness | 10mm | 20mm |
| Cutting gas flow rate | | 250 |
| Shell protection grade | | IP21S |
| Measurement | 440x193x415mm | 515x275x465mm |
| Weight | 18.2kg | 22kg |

Weldmart

Head Office: No 3A, Persiaran Batu Gajah Perdana 7,
Pusat Komersial Batu Gajah Perdana, 31000 Batu
Gajah Perak. Tel: + 012-5052639 Fax: (605) 3665621
E-mail: info@weldmart.com.my