



MIG 200 / MIG 250 / MIG 280

FEATURES:

- Realize rapid continuous spot welding and gas free self- shielded welding to meet the user's efficiency requirements.
- With perfect under- voltage, over – voltage and over- current protection, safe and reliable
- Three - proof air duct structure, full bridge inverter technology, reliability of the welding machine is greatly improved.

Technical Specification: -

Product Type	MIG 280	MIG 315	MIG 270
Input power source	3 ph 380V±15%		1 ph 220V/3 ph 380V±15%
Input frequency	50/60Hz		
Non-Load voltage	65V		
Welding current adjustment range	20-280A	20-315A	20-270A
Arc force current adjustment range	0-100A		
Duty cycle	60%		
Non-load loss	60W	80W	60W
Full load efficiency	85%		
Power factor	0.93		
Insulation class	F		
Shell protection grade	IP21S		
Dimension	520x275x488mm	550x292x607mm	501x278x460mm
Weight	22.7Kg	29.5Kg	20.7Kg

Sales And Services: -

Weldmart

Head Office: No 3A, Persiaran Batu Gajah Perdana 7,
 Pusat Komersial Batu Gajah Perdana, 31000 Batu
 Gajah Perak. Tel: + 012-5052639 Fax:(605) 3665621
 E-mail: info@weldmart.com.my